Docket No. 2003-013-DSK

METHOD AND APPARATUS FOR AUTOMATICALLY CONFIGURING DATA STORAGE SUBSYSTEMS

BACKGROUND OF·THE INVENTION

5

1.   Field of the Invention:

The present invention relates generally to data storage subsystems and particularly to a method and apparatus for automatically configuring data storage

10   subsystems. Still more particularly, the present invention relates to a method and apparatus for automatically replicating a first data storage subsystem's configuration data on a second data storage subsystem.

15

2.   Background of the Invention:

A data storage subsystem is a peripheral of a computer system that is used to store data for the computer system. A data storage subsystem typically

20   includes one or more disk or tape drives and a controller for managing the drives included in the storage subsystem. A data storage subsystem is not a stand alone computer system. Although a storage subsystem does execute an operating system, users may not interact

25   directly with the storage subsystem. A user may interact directly with computer systems, but may not interact directly with a data storage subsystem.

In order for a new data storage subsystem to be used as a peripheral, the data storage subsystem must have a

30   functioning operating system and the subsystem must be

Docket No. 2003-013-DSK

configured. After a data storage subsystem has been configured, it is ready to store user data. When a new data storage subsystem is first turned on, an operating system will start on the storage subsystem. In addition
5   to an operating system executing properly, the storage subsystem must be configured prior to it being used as a peripheral. A data storage subsystem is configured by adding or specifying configuration data for the subsystem. Examples of configuration data include the
10 number and names of volumes in the data storage subsystem, the number and names of partitions in the subsystem, the particular grouping(s) of the volumes and partitions, how the ports of the subsystem are connected, addresses of the various ports, telephone numbers for the
15 ports, a site identifier, and any other data that may be used as configuration data. After the data storage subsystem is configured, it may be used to store user data. A data storage subsystem is not capable of storing user data until the subsystem has been configured.
20   There is a need to replicate a particular data storage subsystem's configuration in order to provide a redundant, backup subsystem. In the prior art, in order to replicate a particular data storage subsystem's configuration, an administrator must first obtain a copy
25 of the configuration data from a first subsystem, and the administrator must then install the copy of the configuration data on a second subsystem. Once the administrator has installed the configuration data on the second storage subsystem, the administrator must restart

Docket No. 2003-013-DSK

the second storage subsystem in order for the
configuration to be complete.

    This manual approach is very time consuming. If the
administrator manually performs this process using a
5   remote host, an expensive resource, the remote host, is
tied up while the administrator completes this process.

    Therefore, the current technology would be improved
by a method and apparatus for automatically replicating a
first data storage subsystem's configuration data on a
10 second data storage subsystem.

Docket No. 2003-013-DSK

SUMMARY OF THE INVENTION

A method and apparatus are disclosed in a data
processing system for automatically replicating a first
5   data storage subsystem's configuration data on a second
data storage subsystem. Storage subsystems are
peripherals of the data processing system and not
standalone computer systems. Storage subsystems are
inaccessible directly by users. A first data storage
10   subsystem is specified as a parent subsystem. The first
data storage subsystem is configured using a first
configuration data. A second data storage subsystem is
specified that is to be configured the same as the first
data storage subsystem. The first or second data storage
15   subsystem automatically initiates a transfer of a copy of
the first configuration data from the first data storage
subsystem to the second data storage subsystem. The
second data storage subsystem configures itself using the
copy of the first configuration data such that the second
20   data storage subsystem is configured the same as the
first data storage subsystem.

The above as well as additional objectives,
features, and advantages of the present invention will
become apparent in the following detailed written
25   description.

Docket No. 2003-013-DSK

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The
5 invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:
10 **Figure 1** is a high level block diagram of a data processing system that includes computer systems and storage subsystems in accordance with the present invention;

Figure 2 depicts a block diagram of a computer
15 system that may be used to implement a computer system in accordance with the present invention; and

Figures 3a-3c together are a high level flow chart that illustrates automatically duplicating a parent storage subsystem's configuration in a clone storage
20 subsystem in accordance with the present invention.

Docket No. 2003-013-DSK

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The present invention is a method and apparatus for automatically replicating a first data storage

5   subsystem's configuration data on a second data storage subsystem. The first data storage subsystem is referred to herein as a parent storage subsystem. The second data storage subsystem is referred to herein as a clone data storage subsystem.

10   When the configuration data of a parent is to be replicated, a storage subsystem that is to be the clone storage subsystem is selected. An automatic configuration facility is enabled on both the parent and the clone. An address is provided to the clone storage

15   subsystem which identifies the parent whose configuration data is to be copied. The address of the clone is also provided to the parent.

A communications link is then established between the parent and clone storage subsystems. This

20   communications link is preferably a dedicated link. At this time the two storage subsystems are physically linked together.

Each storage subsystem includes flags that indicate whether the transfer of the configuration data is to be a

25   push or pull type of transfer. When a push is indicated to both the parent and the clone, the parent sends a copy of its configuration data to the clone. When a pull is indicated to both the parent and clone, the clone contacts the parent and retrieves a copy of the parent's

30   configuration data. Preferably, the configuration data

Docket No. 2003-013-DSK

is transferred in a single file using a file transfer
process. Of course, those skilled in the art will
recognize that other processes may be used.

The automatic configuration facility includes
5   status, completion, and error handling within the
facility itself. In this manner, the facility itself
monitors the data transfer.

The concept of replicating the configuration of a
parent storage subsystem using an automatic configuration
10   utility allows the replication workload to be
internalized to the storage subsystem that is to be the
clone of the parent. Internalization allows for exact
replication, thus reducing errors and increasing
performance during the configuration stage. The process
15   of internalizing and automating the configuration of a
storage subsystem can be achieved by having the storage
subsystem share their configuration data rather than
having the configuration data input into the clone
storage subsystem through conventional means.

20   According to the present invention, a storage
subsystem has the ability to enable the automatic
configuration facility. The facility has an addressing
scheme for each storage subsystem. The facility is
enabled on the storage subsystems through an enabling
25   software utility that is part of the operating system of
the storage subsystem. The addressing scheme for the
storage subsystems is dependent on. the communication link
type use to interconnect the storage subsystems. Each
storage subsystem can be set as either a sender or
30   receiver.

Docket No. 2003-013-DSK

According to the present invention, a transfer of configuration data may be either a push or a pull type of transfer. Configuration data may be pushed from a parent storage subsystem to a storage subsystem that is to be

5 the clone storage subsystem. When a push type of transfer occurs, the parent is set as the sender and the clone is set as the receiver. The parent then initiates the transfer of the copy of the parent's configuration data. When a pull type of transfer occurs, the parent is

10 also set as the sender and the clone is set as the receiver. In the pull arrangement, however, the clone initiates the transfer of the copy of the parent's configuration data.

The present invention automatically configures a

15 data storage subsystem by replicating configuration data. The present invention does not describe replicating user data that might be stored on a parent storage subsystem, but instead describes replicating only the configuration data of a parent storage subsystem. A data storage

20 subsystem may be thought of having three layers of information. In order to be operable, an operating system is required in the storage subsystem that is executed by the controller. The operating system may be thought of as the first layer. The next layer is the

25 configuration data. The storage subsystem must be configured with configuration data before the storage subsystem may be used. Finally, the last layer is the user data. The present invention describes replicating only the configuration data. The present invention does

30 not describe replicating user data.

The present invention provides for quick, accurate, and efficient replications of storage subsystems using an automatic facility. Once enabled, the facility transfers the configuration data between the parent and clone

5   storage subsystems automatically, without user intervention, in order to create a replica of the parent's configuration.

According to an additional feature of the present invention, the automatic replication facility may remain

10   active providing ongoing replication of configuration data from the parent to the clone. Therefore, constant interaction and updates from the parent to the clone would occur.

Figure 1 is a high level block diagram of a data

15   processing system **100** that includes computer systems and storage subsystems in accordance with the present invention. Data processing system **100** includes a computer system **102** and a computer system **104** that are coupled to storage subsystem **106** and storage subsystem

20   **108** via a network **110**. Computer systems **102** and **104** are standalone computer systems. A storage subsystem is not a standalone computer system. A user may not interact directly with the storage subsystem. A user must use one of the computer systems in order to access a storage

25   subsystem.

Each storage subsystem includes a controller and one or more disk or tape drives. For example, storage subsystem **106** includes a control unit **112** and disk drives **114**, **116**, and **118**.

Docket No. 2003-013-DSK

Figure 1 depicts two storage subsystems, subsystems **106** and **120**, that are linked together using a direct communication link **122**. This direct connection **122** may be used to transfer configuration data from one of these

5   storage subsystems to the other. For example, storage subsystem **106** might be a new or existing storage subsystem that has been designated to be the clone or replicated subsystem for storage subsystem **120**.

Figure 2 depicts a block diagram of a computer

10   system in accordance with the present invention. Data processing system **200** may be a symmetric multiprocessor (SMP) system including a plurality of processors **202** and **204** connected to system bus **206**. Alternatively, a single processor system may be employed. Also connected to

15   system bus **206** is memory controller/cache **208**, which provides an interface to local memory **209**. I/O bus bridge **210** is connected to system bus **206** and provides an interface to I/O bus **212**. Memory controller/cache **208** and I/O bus bridge **210** may be integrated as depicted.

20   Peripheral component interconnect (PCI) bus bridge **214** connected to I/O bus **212** provides an interface to PCI local bus **216**. A number of modems may be connected to PCI bus **216**. Typical PCI bus implementations will support four PCI expansion slots or add-in connectors.

25   Additional PCI bus bridges **222** and **224** provide interfaces for additional PCI buses **226** and **228**, from which additional modems or network adapters may be supported. In this manner, data processing system **200** allows connections to multiple network computers. A

30   memory-mapped graphics adapter **230** and hard disk **232** may

Docket No. 2003-013-DSK

also be connected to I/O bus **212** as depicted, either
directly or indirectly.

Those of ordinary skill in the art will appreciate
that the hardware depicted in **Figure 2** may vary. For
5   example, other peripheral devices, such as optical disk
drives and the like, also may be used in addition to or
in place of the hardware depicted. The depicted example
is not meant to imply architectural limitations with
respect to the present invention.

10   **Figures 3a-3c** together are a high level flow chart
that illustrates automatically duplicating a parent
storage subsystem's configuration in a clone storage
subsystem in accordance with the present invention. The
process starts as depicted by block **300** and thereafter
15   passes to block **302** which illustrates a parent storage
subsystem being configured. The parent storage subsystem
is configured using particular configuration data. This
configuration data includes the number of volumes in the
parent storage subsystem, names of each volume, number of
20   partitions in the parent storage subsystem, names of each
partition, grouping of these volumes and partitions,
which ports are connected, the addresses of each port,
telephone numbers, site identifier, and any other
information that may be used to configure a storage
25   subsystem.

Next, block **304** depicts a determination of whether
or not a storage subsystem is to be automatically created
that has the same configuration as the parent storage
subsystem. This second storage subsystem that is to have
30   the same configuration as the parent storage subsystem is

Docket No. 2003-013-DSK

referred to herein as the clone storage subsystem. If a determination is made that no clone is to be created, the process passes back to block **304**. If a determination is made that a clone of the parent storage subsystem is to

5   be created, the process passes to block **306** which illustrates identifying a particular storage subsystem that is to be the clone of the parent storage subsystem.

Block **308** depicts a determination of whether or not the storage subsystem that is to be the clone is a new or

10 existing storage subsystem. If a determination is made that the storage subsystem that is to be the clone is a new storage subsystem, the process passes to block **310** which illustrates powering up the clone storage subsystem. The process then passes to block **312**.

15 Referring again to block **308**, if a determination is made that the storage subsystem that is to be the clone is an existing storage subsystem, the process passes to block **312**.

Block **312** depicts enabling an auto configuration

20 facility on the parent storage subsystem. The facility is enabled on the storage subsystems through an enabling software utility that is part of the operating system of the storage subsystem. Next, block **314** illustrates enabling an auto configuration facility on the clone

25 storage subsystem. The process then passes to block **316** as depicted through connector A. Block **316** illustrates setting parent and clone addresses in the parent storage subsystem. Thereafter, block **318** depicts setting parent and clone addresses in the clone storage subsystem.

The process then passes to block **320** which illustrates connecting the parent and clone storage subsystems together using a communication link. This link may be a phone link, network link, or channel link.

5 In accordance with a preferred embodiment, however, the communication link is a direct connection between the two storage subsystems. Preferably, the communication link is a Fibre Channel link between the two storage subsystems. Using the Fibre Channel link, the two

10 storage subsystems can communication out-of-band with only each other.

Next, block **322** illustrates a determination of whether or not the parent will push a copy of its configuration data to the clone system, or whether the

15 clone system will pull a copy of the parent's configuration data from the parent. If a determination is made that the parent will initiate the transfer of the copy of its configuration data, the process passes to block **323** which depicts setting push flags in the parent

20 and clone storage systems to indicate that the parent will push the copy of the parent's configuration data to the clone. Next, block **324** depicts the parent initiating a transfer of the copy of the parent's configuration data to the clone storage subsystem. Thus, the parent will

25 push the copy of its configuration data to the clone. The process then passes to block **328** as illustrated by connector B.

Referring again to block **322**, if a determination is made that the clone will initiate the transfer of the

30 copy of the parent's configuration data from the parent

to the clone, the process passes to block **325** which illustrates setting pull flags in the parent and clone storage subsystems to indicate that the clone will pull the copy of the parent's configuration data from the

5 parent. Next, block **326** depicts the clone initiating a transfer of the copy of the parent's configuration data from the parent to the clone. Thus, the clone will pull the copy of the parent's configuration data from the parent to the clone. The process then passes to block

10 **328** as illustrated by connector B.

Block **328** depicts the clone receiving the copy of the configuration data from the parent. Next, block **330** illustrates a determination of whether or not the transfer was successful. If a determination is made that

15 the transfer was not successful, the process passes to block **332** which depicts error handling being executed by the auto configuration facility to attempt to correct the problem. Thereafter, block **334** illustrates a determination of whether or not the error handling

20 corrected the problem. If a determination is made that the problem was corrected, the process passes back to block **328**.

Referring again to block **334**, if a determination is made that the problem was not corrected, the process

25 passes to block **336** which depicts the auto configuration facility stopping the transfer of configuration data from the parent to the clone and reporting an error. Thereafter, block **338** illustrates a user correcting the error. The process then passes back to block **322** as

30 depicted by connector C.

Docket No. 2003-013-DSK

Referring again to block **330**, if a determination is made that the transfer was successful, the process passes to block **340** which illustrates the completion of the transfer. Next, block **342** depicts initiating a

5 configuration process on the clone storage subsystem. The configuration process is initiated on the clone by the auto configuration facility upon completion of the transfer. Thereafter, block **344** illustrates restarting the clone storage subsystem with the new configuration

10 data. Thus, the clone storage subsystem and parent storage subsystem now have identical configurations. Block **346**, then, depicts the clone storage subsystem being operational with the same configuration as the parent storage subsystem. The process then terminates as

15 illustrated by block **348**.

It is important to note that while the present invention has been described in the context of a fully functioning data processing system, those of ordinary skill in the art will appreciate that the processes of

20 the present invention are capable of being distributed in the form of a computer readable medium of instructions and a variety of forms and that the present invention applies equally regardless of the particular type of signal bearing media actually used to carry out the

25 distribution. Examples of computer readable media include recordable-type media, such as a floppy disk, a hard disk drive, a RAM, CD-ROMs, DVD-ROMs, and transmission-type media, such as digital and analog communications links, wired or wireless communications

30 links using transmission forms, such as, for example,

Docket No. 2003-013-DSK

radio frequency and light wave transmissions. The computer readable media may take the form of coded formats that are decoded for actual use in a particular data processing system.

5   The description of the present invention has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in

10   the art. The embodiment was chosen and described in order to best explain the principles of the invention, the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are

15   suited to the particular use contemplated.